

COMTELCO

Technical Specification

A4641B, W

LOW PROFILE TRANSIT ANTENNA

Performance: These antennas provide unity gain in a design for heavy duty service. They have a power handling capacity of 200 watts.

Stylish and Durable: These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited ABS plastic and are available in black or white finishes.

Reliable: The brass base is triple plated chrome with a gold plated spring loaded contact.

Standard Mounting: These antennas mate with the standard TAD/NMO type mount, providing an excellent moisture seal even when the antenna is removed.



SPECIFICATIONS:

FREQUENCY RANGE:

A4641-406	406-420MHz
A4641-420	420-430MHz
A4641-430	430-440MHz
A4641-440	440-450MHz
A4641-450	450-460MHz
A4641-460	460-470MHz
A4641-470	470-480MHz
A4641-480	480-490MHz
A4641-490	490-505MHz
A4641-500	500-512MHz

GAIN:	Unity
IMPEDANCE:	50 ohms
POWER RATING:	200 watts
VSWR:	<2.0:1
HOUSING:	ABS UV
BASE:	ABS, Ultrasonic brass insert
CONTACT:	Gold plated spring loaded contact
HEIGHT:	2 3/4"
DIAMETER:	1.5"
MOUNTING:	Standard TAD/NMO type
COLOR: - B:	Black
- W:	White

Vertical Pattern

