

COMTELCO

Technical Specification

A4681- 806 WN, BN

A4681- 896 WN, BN

A4681- 915 WN, BN

806-896 MHz

896-970 MHz

902-928 MHz

LOW PROFILE TAMPERPROOF ANTENNA

Performance: These antennas provide unity gain in a design for heavy duty service. They have a power handling capacity of 200 watts.

Stylish and Durable: These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited ABS plastic and are available in black or white finishes.

Reliable: The heavy duty, chrome plated brass base and "N"connector termination provide rugged and reliable performance.

Tamperproof Mounting: These antennas terminate as an "N" type connector making installation as either a ceiling mount or a bulkhead cabinet type mount through a 5/8" hole.



SPECIFICATIONS:

FREQUENCY RANGE:

A4681-806

806-896MHz

A4681-896

896-970MHz

A4681-915

902-928MHz

GAIN:

2 dBi / Unity

IMPEDANCE:

50 ohms

POWER RATING:

200 watts

VSWR:

<2.0:1 @ 100MHz

BASE:

Heavy duty, triple plated chrome brass

TERMINATION:

"N" female connector

HEIGHT:

2 5/8"

DIAMETER:

1.5"

COLOR:

-W White or -B Black

Vertical Pattern

