
LOW PROFILE CEILING MOUNT ANTENNA

Performance: These antennas provide excellent coverage for ceiling mounted service. They can be used in conjunction with our BSGP white ground plane disk which is shipped standard when these parts are ordered with a – UTCM suffix. They have a high power handling capacity of 100 watts.

Stylish and Durable: These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited white ABS plastic. They blend in well with existing ceiling tile installations.

Reliable: The ABS base has an ultrasonically welded brass insert and a gold plated spring loaded contact.

Mounting: Mount is made simple by using a UTCM mount that terminates as a MINI-UHF connector. Other options are available including a TAN mount that terminates as an “N” connector.



SPECIFICATIONS:

FREQUENCY RANGE:

B16450	450-470MHz
B16806	806-896MHz
B16915	900-930MHz
B16192	1850-1990MHz
B16245	2400-2500MHz

GAIN:	Unity
IMPEDANCE:	50 ohms
POWER RATING:	200 watts
VSWR:	<2.0:1
HOUSING:	ABS
BASE:	ABS, Ultrasonic brass insert
CONTACT:	Gold plated spring loaded contact
HEIGHT:	2 5/8"
DIAMETER:	1.5"
MOUNTING:	Standard TAD/NMO type

UTCM option includes UTCM mount and BSGP ground plane.
Add UTCM suffix. Example: B16245-UTCM

Vertical Pattern

