

# COMTELCO

## Technical Specification

B46192WN, BN

1.85 -1.99 GHz

## LOW PROFILE TAMPERPROOF ANTENNA

**Performance:** These antennas provide unity gain in a design for heavy duty service. They have a power handling capacity of 200 watts.

**Stylish and Durable:** These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited ABS plastic and are available in black or white finishes.

**Reliable:** The brass base is triple plated chrome and terminates as a Mini-UHF connector.

**Tamperproof Mounting:** These antennas terminate as an "N" type connector making installation easy as either a ceiling mount or a bulkhead cabinet type mount through a 5/8" hole.



### SPECIFICATIONS:

<b>FREQUENCY RANGE:</b>	1850-1990MHz
<b>GAIN:</b>	Unity
<b>IMPEDANCE:</b>	50 ohms
<b>POWER RATING:</b>	200 watts
<b>VSWR:</b>	<2.0:1
<b>HOUSING:</b>	ABS UV
<b>HEIGHT:</b>	2 5/8"
<b>DIAMETER:</b>	1.5"
<b>MOUNTING:</b>	"N" Female
<b>COLOR: - B:</b>	Black
<b>- W:</b>	White

### Vertical Pattern

