

COMTELCO

Technical Specification

B4681- 806 BM, WM
B4681- 896 BM, WM
B4681- 915 BM, WM

806-896 MHz
896-970 MHz
902-928 MHz

LOW PROFILE TAMPERPROOF ANTENNA

Performance: These antennas provide unity gain in a design for heavy duty service. They have a power handling capacity of 200 watts.

Stylish and Durable: These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited ABS plastic and are available in black or white finishes.

Reliable: The heavy duty, chrome plated brass base and Mini-UHF connector termination provide rugged and reliable performance.

Tamperproof Mounting: These antennas terminate as a Mini-UHF type connector making installation as either a ceiling mount or a bulkhead cabinet type mount through a 3/8" hole.



SPECIFICATIONS:

FREQUENCY RANGE:

A4681-806 806-896MHz

A4681-896 896-970MHz

A4681-915 902-928MHz

GAIN: 2 dBi / Unity

IMPEDANCE: 50 ohms

POWER RATING: 200 watts

VSWR: <2.0:1 @ 100MHz

BASE: Heavy duty, triple plated chrome brass

TERMINATION: Mini- UHF connector

HEIGHT: 2 5/8"

DIAMETER: 1.5"

COLOR: -W White or -B Black

Vertical Pattern

