

# COMTELCO

## Technical Specification

B4681- 806 WN, BN  
B4681- 896 WN, BN  
B4681- 915 WN, BN

806-896 MHz  
896-970 MHz  
902-928 MHz

## LOW PROFILE TAMPERPROOF ANTENNA

**Performance:** These antennas provide unity gain in a design for heavy duty service. They have a power handling capacity of 200 watts.

**Stylish and Durable:** These antennas are manufactured using the finest materials and finishes available. The covers are molded using UV inhibited ABS plastic and are available in black or white finishes.

**Reliable:** The heavy duty, chrome plated brass base and "N"connector termination provide rugged and reliable performance.

**Tamperproof Mounting:** These antennas terminate as an "N" type connector making installation as either a ceiling mount or a bulkhead cabinet type mount through a 5/8" hole.



### SPECIFICATIONS:

#### FREQUENCY RANGE:

A4681-806

806-896MHz

A4681-896

896-970MHz

A4681-915

902-928MHz

**GAIN:**

2 dBi / Unity

**IMPEDANCE:**

50 ohms

**POWER RATING:**

200 watts

**VSWR:**

<2.0:1 @ 100MHz

**BASE:**

Heavy duty, triple plated chrome brass

**TERMINATION:**

"N" female connector

**HEIGHT:**

2 5/8"

**DIAMETER:**

1.5"

**COLOR:**

-W White or -B Black

### Vertical Pattern

