

# COMTELCO

## Technical Specification

## BS450XL6

### 406-512 MHz 6dBd Gain

### BASE STATION ANTENNA

**Reliable Performance:** Rated at 250 watts and 6dB gain, you can expect years of continuous service.

**Rugged Construction:** The radiating elements are constructed of copper & copper alloy. They are encased in a fiberglass radome for total environmental protection.

**Weatherproof:** The fiberglass radome is ultraviolet inhibited. The heavy wall aluminum mounting sleeve is epoxy coated for superior weather protection.

**Lightweight:** These antennas are lightweight at less than 8 lbs. but are designed to easily withstand winds of over 100 MPH.

**Simple installation:** Using the optional BSMNT2 mounting kit, installation takes only minutes.

#### ELECTRICAL SPECIFICATIONS:

##### FREQUENCY RANGE:

BS450XL6-AB	406-440MHz
BS450XL6-BCD	440-480MHz
BS450XL6-C	450-470MHz
BS450XL3-DE	480-512MHz

<b>GAIN:</b>	6dBd
<b>VSWR:</b>	<2.0:1
<b>BANDWIDTH:</b>	>20 MHz
<b>POWER RATING:</b>	250 watts
<b>IMPEDANCE:</b>	50 ohms
<b>VERT BEAMWIDTH:</b>	20 degrees

##### MECHANICAL SPECIFICATIONS:

<b>RADIATOR:</b>	Internal copper alloy elements
<b>RADOME:</b>	White UV inhibited fiberglass
<b>MOUNTING SLEEVE:</b>	1.35" dia. heavy wall epoxy coated
<b>TERMINATION:</b>	Female N standard, pigtail optional
<b>LENGTH:</b>	96"
<b>WEIGHT:</b>	8 lbs.
<b>FLAT PLATE AREA:</b>	.44 ft <sup>2</sup>
<b>WIND RATING:</b>	125 MPH
<b>LATERAL THRUST:</b>	29.7 lbs.



#### Vertical Pattern

